

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053855 A1

(51) International Patent Classification⁷: **B04C 5/10**,
5/13, A47L 9/16

Wiltshire SN15 3DZ (GB). **EDDINGTON, Robin**
[GB/GB]; Filands Farm, Filands, Malmesbury, Wiltshire
SN16 9JN (GB).

(21) International Application Number:
PCT/GB2004/004303

(74) Agents: **SMITH, Gillian, Ruth et al.**; Intellectual Prop-
erty Department, Dyson Limited, Tetbury Hill, Malmes-
bury, Wiltshire SN16 ORP (GB).

(22) International Filing Date: 11 October 2004 (11.10.2004)

(25) Filing Language: English

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(26) Publication Language: English

(30) Priority Data:
0326102.1 8 November 2003 (08.11.2003) GB

(71) Applicant (*for all designated States except US*): **DYSON
TECHNOLOGY LIMITED** [GB/GB]; Tetbury Hill,
Malmesbury, Wiltshire SN16 ORP (GB).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **STRUTT, Ben-
jamin, John** [GB/GB]; 110 Wood Lane, Chippenham,

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,

[Continued on next page]

(54) Title: CYCLONIC SEPARATING APPARATUS



(57) Abstract: The invention provides separating apparatus (100) comprising a separating chamber (132) in which cyclonic separation is able to take place, an inlet (118) to the separating chamber (132) and a shroud (124) comprising a wall (126) having a multiplicity of through-holes (128) forming an outlet from the separating chamber (132), the shroud (124) further comprising a lip (130; 130') extending from the wall (126) into the separating chamber (132), characterized in that lip (130; 130') has a plurality of apertures (136) therethrough. The provision of apertures (136) in the depending lip (130; 130') allows the airflow to be drawn through the apertures (136) whilst it is still in the separating chamber (132). This has the effect of capturing some of the dirt and dust which remains entrained within the airflow so that it collects on the upstream side (130a) of the lip (130; 130'). Thus the shroud through-holes (128) are presented with less entrained dirt and dust and the risk of the through-holes (128) becoming blocked is reduced.

WO 2005/053855 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *with amended claims*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*